

Product data sheet

Specifications



Renova - double socket outlet - 2P + E - 2-circuits - 16 A - 250 V - black

WDE011326

Main

Range	Renova
Product or component type	Socket-outlet
Device presentation	Mechanism with fixing frame
Quantity per set	Set of 5
Product compatibility	To be completed with Renova frame

Complementary

Socket number	2
Device mounting	Flush
Outlet poles configuration	2P + E
Outlet standard description	Side earth
Outlet standard	Schuko
Rated current	16 A
[Ue] rated operational voltage	250 V AC
Colour tint	Black (NCS S 9000-N)
Connections - terminals	Screw terminals
Shape of screw head	Pozidriv No 1 and combi
Clamping connection capacity	1 x 1.5...2 x 2.5 mm ² for solid cable(s) 1 x 1.5...2 x 2.5 mm ² for solid stranded cable(s)
Material	PC/ABS
Fixing mode	By screws and claws
Width	71 mm
Height	92 mm
Embedding depth	22 mm
Projecting depth	22 mm

Environment

Standards	IEC 60884-1 SS 4280834 SFS 5610:2004 NEK 502:2006
Product certifications	FIMKO

	NEMKO SEMKO
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	86 g
Package 1 Height	5 cm
Package 1 width	7 cm
Package 1 Length	9.4 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Weight	508 g
Package 2 Height	10.6 cm
Package 2 width	9.4 cm
Package 2 Length	26 cm
Unit Type of Package 3	CAR
Number of Units in Package 3	60
Package 3 Weight	6.53 kg
Package 3 Height	34.2 cm
Package 3 width	29.2 cm
Package 3 Length	39.2 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile