

Datasheet



ENSTO CLAMPO PRO ENSTO

Terminal block Grey, 3-pole, Al/Cu 50 mm²

REF. KE61.03 | 1933063 | EAN. 6418677191824

3-pole, grey, Al 6-50 mm², Cu 2.5-50 mm²

> [Visit e-catalogue](#)

Main description:

3-pole, grey, Al 6-50 mm², Cu 2.5-50 mm²

Description

Ensto Clampo Pro is a comprehensive universal terminal series for Al/Cu conductors of 2.5 – 240 mm².

Technical characteristics

Connectable conductor cross section fine-strand without cable end sleeve (Min-Max)	25 - 35 mm ²
Connectable conductor cross section fine-strand with cable end sleeve (Min-Max)	2.5 - 35 mm ²
Connectable conductor cross section multi-wired (Min-Max)	2.5 - 50 mm ²
Rated current I _n	145 A
Rated voltage	800 V
Type of electrical connection 1	Screw connection
Type of electrical connection 2	Screw connection
Number of levels	1
Number of clamp positions per level	6

Mounting method	DIN rail (top hat rail) 35 mm
Material insulation body	Thermoplastic
Operating temperature (Min-Max)	-5 - 80 °C
Width	49.5 mm
Height	43 mm
Depth	49 mm
Explosion-tested version 'Ex e'	No
Colour	Grey
Inflammability class of insulation material according to UL 94	V2

Documentation

Technical documentation

IG_Clampo Pro.pdf | PDF (0.51Mo)

CAD & Design specs / BIM

3D_KE61-03_PK2_V1.stp | IFC (9.02Mo)

2D_KE61.03_2.dxf | DXF (1.42Mo)

 2D_KE61.03.dwg | DWG (0.34Mo)

 DD_KE61.03.pdf | PDF (0.27Mo)

Agreements & certificates

 CE_KE61_2024_FI.pdf | PDF (0.05Mo)

 LGRP-02239-V01.01-EN.pdf | PDF (0.83Mo)

 CE_KE61_2024_EN.pdf | PDF (0.05Mo)