


Inspire White 4300lm 4000K Ra>80 DALI / Push Dim

Article code: 212083
EAN: 7021982120831



Electrical

Wattage: 34W
System wattage: 34W
Voltage: 230V
Max. luminaires per circuit breaker: B10: 8, B16: 13, C10: 12, C16: 20

Light technic

Type of light source: LED (not exchangeable)
Luminous flux: 4300lm
Efficacy: 126 lm/W
Colour temperature: 4000K
Colour rendering (CRI): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L80/B20>100,000
Lifetime: L90>50,000
Light distribution: Direct/Indirect 50/50%
Optic: Cubic Optic Black
UGR: UGR<10
Photobiological safety: RG 1

Control/Dimming

Type: DALI / Push Dim

Protection

Luminaire class: Class I

Energy and approvals

Energy class (2021-): D
Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Aluminium
Colour: White
Optics: Polycarbonat (PC)

Mounting/Connection




Mounting: Suspended, Indoor
Wire set: 2x2m wire kit
Cable: Cable 5x0,75mm² 2,5m

Dimensions (mm)

Length (mm) L: 1241
Width (mm) W: 38
Height (mm) H: 67
Weight (brutto/netto): 2.7 / 2.5

Packaging

Packing dimensions (mm): 1250 x 42 x 80



7 0 2 1 9 8 2 1 2 0 8 3 1