











This item includes:

 Item No.: 221-412 Splicing connector with levers; for all conductor types; max. 4 mm ² ; 2-conductor; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm ² ; transparent	 Item No.: 221-413 Splicing connector with levers; for all conductor types; max. 4 mm ² ; 3-conductor; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm ² ; transparent	 Item No.: 221-415 Splicing connector with levers; for all conductor types; max. 4 mm ² ; 5-conductor; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm ² ; transparent	 Item No.: 2273-202 PUSH WIRE® splicing connector; for solid conductors; max. 2.5 mm ² ; 2-conductor; transparent housing; white cover; Surrounding air temperature: max 60°C (T60); 2,50 mm ² ; transparent
 Item No.: 2273-203 PUSH WIRE® splicing connector; for solid conductors; max. 2.5 mm ² ; 3-conductor; transparent housing; orange cover; Surrounding air temperature: max 60°C (T60); 2,50 mm ² ; transparent	 Item No.: 2273-208 PUSH WIRE® splicing connector; for solid conductors; max. 2.5 mm ² ; 8-conductor; transparent housing; light gray cover; Surrounding air temperature: max 60°C (T60); 2,50 mm ² ; transparent	 Item No.: 207-1332 Gelbox; Branch; for cables; with gel; 221, 2x73 Series; max. 4 mm ² connectors; without splicing connectors; Size 2; gray	 Item No.: 207-1331 Gelbox; Branch; for cables; with gel; 221, 2x73 Series; max. 4 mm ² connectors; without splicing connectors; Size 1; gray

Notes	NOTICE: Observe installation and safety instructions!
General safety instructions	<ul style="list-style-type: none">• Only to be used by electricians!• Do not work under voltage/load!• Use only for proper use!• Observe national regulations/standards/guidelines!• Observe technical specifications for the products!• Observe the number of permissible potentials!• Do not use damaged/dirty components!• Observe conductor types, cross-sections and strip lengths!• Insert conductor until it hits the product's backstop!• Use original accessories! <p>To be sold only with installation instructions!</p>



Physical data		
Width		259 mm / 10.197 inches
Height		42 mm / 1.654 inches
Depth		106 mm / 4.173 inches

Material data		
Note (material data)		Information on material specifications can be found here
Fire load		4.124 MJ
Weight		381.1 g

Commercial data		
PU (SPU)		1 pcs
Packaging type		Box
Country of origin		DE
GTIN		4066966194906
Customs tariff number		85369010000

Product classification		
UNSPSC		39121409
ETIM 9.0		EC000446
ETIM 8.0		EC000446
ECCN		NO US CLASSIFICATION

Environmental Product Compliance		
RoHS Compliance Status		Compliant,No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 887-805

↓