



# TrueForce - LED HID HPL

## **TForce LED HPL ND 57-42W E40 830**

Philips TrueForce LED lamps provide an easy LED solution with a fast payback to replace High-Intensity Discharge (HID) and High Pressure Sodium (SON) lamps. These post-top lamps bring the energy efficiency and long lifetime benefits of LED to HID replacement, delivering instant savings for a low initial investment. With the right lamp size and light distribution, customers can easily retrofit TrueForce LED lamps into their existing HPL and SON system, thereby enhancing the light quality with LED HID, without having to change the fixtures or sacrifice the light effect.

#### **Warnings and Safety**

· Installation should always be performed by a qualified electrician or installer. Use the installation guide for instructions

### **Product data**

| General Information                   |                                       |
|---------------------------------------|---------------------------------------|
| Cap-Base                              | E40 [E40]                             |
| CE mark                               | Yes                                   |
| EU RoHS compliant                     | Yes                                   |
| Nominal lifetime                      | 50,000 hour(s)                        |
| Switching Cycle                       | 50,000                                |
| Lighting Technology                   | LED                                   |
| Flux measurement reference            | Sphere                                |
|                                       |                                       |
| Light Technical                       |                                       |
| Color Code                            | 830 [CCT of 3000K]                    |
| Beam Angle (Nom)                      | 360 degree(s)                         |
| Luminous Flux                         | 5,700 lumen                           |
| Color Designation                     | White (WH)                            |
| Correlated Color Temperature (Nom)    | 3000 K                                |
| · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · |

| Luminous Efficacy (rated) (Nom)       | 135 lm/W    |
|---------------------------------------|-------------|
| Color Consistency                     | <6          |
| Color rendering index (CRI)           | 80          |
| LLMF At End Of Nominal Lifetime (Nom) | 70 %        |
|                                       |             |
| Operating and Electrical              |             |
| Line Frequency                        | 50 to 60 Hz |
| Input Frequency                       | 50 to 60 Hz |
| Power Consumption                     | 42 W        |
| Lamp Current (Nom)                    | 186 mA      |
| Wattage Equivalent                    | 125 W       |
| Starting Time (Nom)                   | 0.45 s      |
| Warm-up time to 60% light             | 0.45 s      |
| Power Factor (Fraction)               | 0.95        |


Datasheet, 2023, May 5 data subject to change

# TrueForce - LED HID HPL

| Voltage (Nom)                 | 220-240 V       |
|-------------------------------|-----------------|
|                               |                 |
| Temperature                   |                 |
| Ambient temperature range     | -40 °C to 55 °C |
| T-Case Maximum (Nom)          | 65 °C           |
|                               |                 |
| Controls and Dimming          |                 |
| Dimmable                      | No              |
|                               |                 |
| Mechanical and Housing        |                 |
| Bulb Finish                   | Clear           |
| Bulb Shape                    | Others          |
|                               |                 |
| Approval and Application      |                 |
| Energy Consumption kWh/1000 h | 42 kWh          |


| EPREL Registration Number       | 403,605                          |
|---------------------------------|----------------------------------|
|                                 |                                  |
| Product Data                    |                                  |
| Full product code               | 871869963826900                  |
| Order product name              | TForce LED HPL ND 57-42W E40 830 |
| Order code                      | 929002006702                     |
| Numerator - Quantity Per Pack   | 1                                |
| Numerator - Packs per outer box | 6                                |
| Material number (12NC)          | 929002006702                     |
| Net weight                      | 0.500 kg                         |
| Full product name               | TForce LED HPL ND 57-42W E40 830 |
| EAN/UPC - Case                  | 8718699638276                    |

# Dimensional drawing




| Product                          | D     | С      |
|----------------------------------|-------|--------|
| TForce LED HPL ND 57-42W E40 830 | 84 mm | 191 mm |

#### Photometric data









## TrueForce - LED HID HPL


#### Photometric data



Light Distribution Diagram - TForce LED HPL ND 57-42W E40 830

## Lifetime





Life Expectancy Diagram - TForce LED HPL ND 57-42W E40 830

Lumen Maintenance Diagram - TForce LED HPL ND 57-42W E40 830



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.