



# MASTER VALUE LEDspot MV

## MAS LED spot VLE D 650lm GU10 930 120D

Delivering a warm, halogen-like accent beam, MASTER VALUE is a perfect fit for spot lighting. Thanks to its high CRI, it realizes more natural colors, creating cozy and comfortable ambiances for residential and hospitality projects, and emphasizing the beauty of merchandise in retail. These LED spots MV GU10 have the familiar look and feel of spot lamps, keeping the classic beauty of glass spots and adding the strong performance of LED technology. The dimming function enables you to create the atmosphere you desire, and it works with broad selection of dimmers. MASTER VALUE also offers more energy savings than normal LED spots.

### Warnings and Safety

- Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Not intended for use with emergency light fixtures or exit lights

### Product data

General Information	
Cap-Base	GU10 [GU10]
Nominal lifetime	25,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Sphere
Light Technical	
Color Code	930 [CCT of 3000K]
Beam Angle (Nom)	120 degree(s)
Luminous Flux	650 lumen


Luminous Intensity (Nom)	200 cd
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	104.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz

MASTER VALUE LEDspot MV

Power Consumption	6.2 W
Lamp Current (Nom)	33 mA
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.88
Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	80 °C
Controls and Dimming	
Dimmable	Only with specific dimmers
Mechanical and Housing	
Bulb Shape	PAR16 [PAR 2 inch/50mm]
Approval and Application	
Suitable For Accent Lighting	No



Energy Consumption kWh/1000 h	7 kWh
EPREL Registration Number	391,917
EU RoHS compliant	Yes
Product Data	
Full product code	871869970609800
Order product name	MAS LED spot VLE D 650lm GU10 930 120D
Order code	929002210002
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material number (12NC)	929002210002
Full product name	MAS LED spot VLE D 650lm GU10 930 120D
EAN/UPC - Case	8718699706531

Dimensional drawing



Product	D	C
MAS LED spot VLE D 650lm GU10 930 120D	50 mm	54 mm


Photometric data



Light Distribution Diagram - MAS LED spot VLE D 650lm GU10 930 120D


# MASTER VALUE LEDspot MV

## Photometric data




Spectral Power Distribution Colour - MAS LED spot VLE D 650lm GU10 930 120D

## Lifetime



Lumen Maintenance Diagram - MAS LED spot VLE D 650lm GU10 930 120D



Life Expectancy Diagram - MAS LED spot VLE D 650lm GU10 930 120D

