



## Main

|                           |                 |
|---------------------------|-----------------|
| Range                     | TeSys           |
| Product name              | TeSys CAD       |
| Product or component type | Control relay   |
| Device short name         | CAD             |
| Contactor application     | Control circuit |

## Complementary

|                                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|---------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Utilisation category                        | DC-13<br>AC-15<br>AC-14                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Pole contact composition                    | 5 NO                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| [Ue] rated operational voltage              | ≤ 690 V AC 25...400 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Control circuit type                        | AC at 50/60 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| [Uc] control circuit voltage                | 110 V AC 50/60 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| [Uimp] rated impulse withstand voltage      | 6 kV conforming to IEC 60947                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| [Ith] conventional free air thermal current | 10 A (at 60 °C)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Irms rated making capacity                  | 140 A AC conforming to IEC 60947-5-1<br>250 A DC conforming to IEC 60947-5-1                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| [Icw] rated short-time withstand current    | 100 A - 1 s<br>120 A - 500 ms<br>140 A - 100 ms                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Associated fuse rating                      | 10 A gG conforming to IEC 60947-5-1                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| [Ui] rated insulation voltage               | 600 V UL certified<br>600 V CSA certified<br>690 V conforming to IEC 60947-5-1                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Mounting support                            | Rail<br>Plate                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Connections - terminals                     | Screw clamp terminals 1 cable(s) 1...4 mm <sup>2</sup> flexible without cable end<br>Screw clamp terminals 2 cable(s) 1...4 mm <sup>2</sup> flexible without cable end<br>Screw clamp terminals 1 cable(s) 1...4 mm <sup>2</sup> flexible with cable end<br>Screw clamp terminals 2 cable(s) 1...2.5 mm <sup>2</sup> flexible with cable end<br>Screw clamp terminals 1 cable(s) 1...4 mm <sup>2</sup> solid without cable end<br>Screw clamp terminals 2 cable(s) 1...4 mm <sup>2</sup> solid without cable end |
| Tightening torque                           | 1.2 N.m - on screw clamp terminals - with screwdriver Philips No 2                                                                                                                                                                                                                                                                                                                                                                                                                                               |

1.2 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm

|                                 |                                                                                                                                                                                                                                                                                                                      |
|---------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Control circuit voltage limits  | 0.3...0.6 Uc (-40...70 °C):drop-out AC 50/60 Hz<br>0.8...1.1 Uc (-40...60 °C):operational AC 50 Hz<br>0.85...1.1 Uc (-40...60 °C):operational AC 60 Hz<br>1...1.1 Uc (60...70 °C):operational AC 50/60 Hz                                                                                                            |
| Operating time                  | 12...22 ms coil energisation and NO closing<br>4...12 ms coil de-energisation and NO opening                                                                                                                                                                                                                         |
| Mechanical durability           | 30 Mcycles                                                                                                                                                                                                                                                                                                           |
| Maximum operating rate          | 180 cyc/mn                                                                                                                                                                                                                                                                                                           |
| Inrush power in VA              | 70 VA 50 Hz (at 20 °C)                                                                                                                                                                                                                                                                                               |
| Hold-in power consumption in VA | 8 VA 50 Hz (at 20 °C)                                                                                                                                                                                                                                                                                                |
| Minimum switching voltage       | 17 V                                                                                                                                                                                                                                                                                                                 |
| Minimum switching current       | 5 mA                                                                                                                                                                                                                                                                                                                 |
| Non-overlap time                | 1.5 ms on energisation between NC and NO contact<br>1.5 ms on de-energisation between NC and NO contact                                                                                                                                                                                                              |
| Insulation resistance           | > 10 MOhm                                                                                                                                                                                                                                                                                                            |
| Mechanical robustness           | Shocks control relay open: 10 Gn for 11 ms conforming to IEC 60068-2-27<br>Shocks control relay closed: 15 Gn for 11 ms conforming to IEC 60068-2-27<br>Vibrations control relay open: 2 Gn, 5...300 Hz conforming to IEC 60068-2-6<br>Vibrations control relay closed: 4 Gn, 5...300 Hz conforming to IEC 60068-2-6 |
| Height                          | 77 mm                                                                                                                                                                                                                                                                                                                |
| Width                           | 45 mm                                                                                                                                                                                                                                                                                                                |
| Depth                           | 84 mm                                                                                                                                                                                                                                                                                                                |
| Net weight                      | 0.58 kg                                                                                                                                                                                                                                                                                                              |

## Environment

|                                       |                                                                   |
|---------------------------------------|-------------------------------------------------------------------|
| Standards                             | BS 4794<br>EN 60947-5<br>IEC 60947-5-1<br>NF C 63-140<br>VDE 0660 |
| Product certifications                | UL<br>CSA                                                         |
| IP degree of protection               | IP2x front face conforming to VDE 0106                            |
| Protective treatment                  | TH conforming to IEC 60068                                        |
| Ambient air temperature for operation | -40...60 °C<br>60...70 °C with derating                           |
| Ambient air temperature for storage   | -60...80 °C                                                       |
| Operating altitude                    | 0...3000 m                                                        |

## Packing Units

|                              |            |
|------------------------------|------------|
| Unit Type of Package 1       | PCE        |
| Number of Units in Package 1 | 1          |
| Package 1 Weight             | 356 g      |
| Package 1 Height             | 5 cm       |
| Package 1 width              | 9.2 cm     |
| Package 1 Length             | 11.2 cm    |
| Unit Type of Package 2       | S02        |
| Number of Units in Package 2 | 20         |
| Package 2 Weight             | 7.428 kg   |
| Package 2 Height             | 15 cm      |
| Package 2 width              | 30 cm      |
| Package 2 Length             | 40 cm      |
| Unit Type of Package 3       | P06        |
| Number of Units in Package 3 | 320        |
| Package 3 Weight             | 129.099 kg |

|                  |       |
|------------------|-------|
| Package 3 Height | 80 cm |
| Package 3 width  | 80 cm |
| Package 3 Length | 60 cm |

### Offer Sustainability

|                            |                                                                                                                             |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                           |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>                                                                            |
| Mercury free               | Yes                                                                                                                         |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information       |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 12 months |
|----------|-----------|