

## Inspire R White 150 470lm 3000K Ra 98 Trailing edge dimming

Article code: 212417  
EAN: 7021982124174



### Electrical

System wattage: 8W  
Voltage: 220-240V  
Max. luminaires per circuit breaker: B10: 32, B16: 50, C10: 52, C16: 85

### Light technic

Type of light source: LED  
Luminous flux: 470lm  
Efficacy: 59 lm/W  
Colour temperature: 3000K  
Colour rendering (CRI): Ra 98  
MacAdams factor: SDCM: 2  
Lifetime: L90/B10>100,000  
Light distribution: Direct  
Optic: Lens  
Beam angle: 55°  
UGR: UGR<19  
Photobiological safety: RG 1

### Control/Dimming

Type: Trailing edge dimming

### Protection

Luminaire class: Class II SELV

### Energy and approvals

Contains light source of energy class: E  
Breeam: Fulfils Hea 01 for flicker free lighting

### Materials and finish

Housing: Aluminium  
Colour: White (RAL 9003)

### Mounting/Connection

Mounting: Recessed, Indoor  
Module: Recessed  
Connection: Screwless terminal block

### Dimensions

Length (mm) L: 163  
Width (mm) W: 62  
Height (mm) H: 40  
Weight (kg) gross/net: 0.406 / 0.31

### Packaging

Packing dimensions (mm): 177 x 121 x 73

