

Rax Soft Square 200



Rax Soft Square 200 Satin 4000K Ra>80 Trailing edge dimming

Article code: 212581
EAN: 7021982125812



Electrical

System wattage: 19W
Voltage: 220-240V
Frequency (Hz): 50/60Hz

Light technic

Type of light source: LED
Colour temperature: 4000K
Colour rendering (CRI): Ra>80
MacAdams factor: SDCM: 2
Lifetime: L90/B10>100,000
Light distribution: Direct
Optic: Satin Matt Reflector
Beam angle: 62°
UGR: UGR<19 opptil 600 mA

Control/Dimming

Type: Trailing edge dimming

Protection

Luminaire class: Class II SELV

Materials and finish

Housing: Flame retardant polycarbonate
Colour: White/Satin mat
Optics: Polycarbonat (PC)

Mounting/Connection



Mounting: Recessed, Indoor
Cable: Cable 5x0,75mm²
Connection: 3 pol Linect / screwless terminal block

Dimensions

Length (mm) L: 216
Width (mm) W: 216
Height (mm) H: 93
Ceiling void depth (mm): 90
Weight (kg) gross/net: 1.225 / 1

Packaging

Packing dimensions (mm): 260 x 235 x 100



7 0 2 1 9 8 2 1 2 5 8 1 2