## Product data sheet Characteristics

# NSYCRN108250P

Spacial CRN plain door with mount.plate. H1000xW800xD250 IP66 IK10 RAL7035...





#### Main

| IVIAIII                     |   |           |
|-----------------------------|---|-----------|
| Range                       | Spacial   |           |
| Product name                | Spacial CRN   | į         |
| Application                 | Multi-purpose   |           |
| Category                    | Compact enclosure   | , s       |
| Enclosure nominal height    | 1000 mm   |           |
| Enclosure nominal width     | 800 mm  |           |
| Enclosure nominal depth     | 250 mm  |           |
| Installation accessory type | Wall-mounting   | 41<br>6   |
| Device composition          | 1 body<br>1 door with lock<br>1 mounting plate<br>2 cable gland plate: bottom | o orinina |
| Door type                   | Plain   |           |
| Mounting plate description  | Plain   |           |

### Complementary

| Back welded with double profile forming a protected sealed area<br>Sides made from a single folded section |  |
|--|--|
| Front face: 1 door(s)  |  |
| Reversible (120 °)   |  |
| 3 mm double-bar lock   |  |
| Standard   |  |
| Front  |  |
| Door by hinges<br>Cable gland plate by screws<br>Mounting plate by fixing element                          |  |
| Enclosure: steel<br>Mounting plate: galvanised steel   |  |
|  | Sides made from a single folded section  Front face: 1 door(s)  Reversible (120 °)  3 mm double-bar lock  Standard  Front  Door by hinges Cable gland plate by screws Mounting plate by fixing element  Enclosure: steel |

| Surface finish         | Enclosure: epoxy-polyester powder |
|------------------------|-----------------------------------|
| Colour                 | Enclosure: grey (RAL 7035)        |
| Standards              | IEC 62208                         |
| Product certifications | CUL<br>UL<br>DNV-GL               |
| Net weight             | 42 kg                             |

#### Environment

| IP degree of protection | IP66 conforming to IEC 60529 |
|-------------------------|------------------------------|
| IK degree of protection | IK10 conforming to IEC 62262 |

## Packing Units

| Unit Type of Package 1       | PCE       |
|------------------------------|-----------|
| Number of Units in Package 1 | 1         |
| Package 1 Weight             | 43.747 kg |
| Package 1 Height             | 26.5 cm   |
| Package 1 width              | 81 cm     |
| Package 1 Length             | 101 cm    |

## Offer Sustainability

| Sustainable offer status   | Green Premium product   |  |
|----------------------------|---|--|
| REACh Regulation           | REACh Declaration   |  |
| REACh free of SVHC         | Yes   |  |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration  |  |
| Mercury free               | Yes   |  |
| RoHS exemption information | Yes   |  |
| China RoHS Regulation      | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information  |  |
| Environmental Disclosure   | Product Environmental Profile   |  |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |  |

#### Contractual warranty

| Warranty | 18 months |
|----------|-----------|